

MAJOR TECHNICAL SPECIFICATIONS

Item		Area	U.S.A. and Mexico		U.S.A. and Canada		
Body Type			Wagon				
Vehicle Grade			SR5	Limited	SR5	Limited	
Model Code			UPK60L-GKTSKA	UPK60L-GKTLKA	UPK65L-GKTSKA	UPK65L-GKTLKA	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)
	Wheel Base	mm (in.)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)	
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)
	Effective Head Room	Front	mm (in.)	—	—	—	—
		Rear No. 1	mm (in.)	—	—	—	—
		Rear No. 2	mm (in.)	—	—	—	—
	Effective Leg Room	Front	mm (in.)	—	—	—	—
		Rear No. 1	mm (in.)	—	—	—	—
		Rear No. 2	mm (in.)	—	—	—	—
	Shoulder Room	Front	mm (in.)	—	—	—	—
		Rear No. 1	mm (in.)	—	—	—	—
		Rear No. 2	mm (in.)	—	—	—	—
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
Min. Running Ground Clearance	mm (in.)	—	—	—	—		
Angle of Approach	degrees	26.9	26.9	27.1	27.1		
Angle of Departure	degrees	—	—	—	—		
Curb Weight	Front	kg (lb)	1263 (2785)	1263 (2785)	1376 (3035)	1374 (3030)	
	Rear	kg (lb)	1308 (2885)	1317 (2905)	1331 (2935)	1335 (2945)	
	Total	kg (lb)	2571 (5670)	2580 (5690)	2707 (5970)	2710 (5975)	
Gross Vehicle Weight	Front	kg (lb)	1383 (3049)	1366 (3013)	1487 (3279)	1473 (3248)	
	Rear	kg (lb)	1774 (3911)	1790 (3947)	1805 (3981)	1819 (4012)	
	Total	kg (lb)	3157 (6960)	3157 (6960)	3293 (7260)	3293 (7260)	
Fuel Tank Capacity	ℓ (U.S.gal., Imp.gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)		
Luggage Compartment Capacity (behind Front / Rear No. 1 / Rear No. 2 Seats)	m ³ (cu.ft.)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)		
Performance	Max. Speed	km / h (mph)	180 (111)	180 (111)	180 (111)	180 (111)	
	Max. Cruising Speed	km / h (mph)	180 (111)	180 (111)	180 (111)	180 (111)	
	Max. Permissible Speed	1st Gear	km / h (mph)	61 (37)	61 (37)	61 (37)*4, 23 (14)*5	61 (37)*4, 23 (14)*5
		2nd Gear	km / h (mph)	105 (65)	105 (65)	105 (65)*4, 40 (24)*5	105 (65)*4, 40 (24)*5
		3rd Gear	km / h (mph)	154 (95)	154 (95)	154 (95)*4, 58 (36)*5	154 (95)*4, 58 (36)*5
		4th Gear	km / h (mph)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		5th Gear	km / h (mph)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		6th Gear	km / h (mph)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	—	—	—	—
		Curb to Curb	m (ft.)	—	—	—	—
Engine	Engine Type		IUR-FE	IUR-FE	IUR-FE	IUR-FE	
	Valve Mechanism		32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	
	Bore × Stroke	mm (in.)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	
	Displacement	cm ³ (cu.in.)	4608 (281.2)	4608 (281.2)	4608 (281.2)	4608 (281.2)	
	Compression Ratio		10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	
	Fuel System		SFI	SFI	SFI	SFI	
	Octane Rating		87 or higher	87 or higher	87 or higher	87 or higher	
	Max. Output (SAE-NET)	kW / rpm (HP / rpm)	231 / 5600 (310 / 5600)	231 / 5600 (310 / 5600)	231 / 5600 (310 / 5600)	231 / 5600 (310 / 5600)	
Max. Torque (SAE-NET)	N·m / rpm (ft·lb / rpm)	443 / 3400 (327 / 3400)	443 / 3400 (327 / 3400)	443 / 3400 (327 / 3400)	443 / 3400 (327 / 3400)		
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64	12 - 64	
	Generator Output	Watts	1560, 1800*3, 2160*2	1800, 2160*2	1560, 1800*3, 2160*2	1800, 2160*2	
	Starter Output	kW	1.6 / 2.0*7	1.6 / 2.0*7	1.6 / 2.0*7	1.6 / 2.0*7	
	Clutch Type		—	—	—	—	
Chassis	Transmission Type		A760E	A760E	A760F	A760F	
	Gear Ratio	In 1st		3.520	3.520	3.520	3.520
		In 2nd		2.042	2.042	2.042	2.042
		In 3rd		1.400	1.400	1.400	1.400
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.716	0.716	0.716	0.716
		In 6th		0.586	0.586	0.586	0.586
		In Reverse		3.224	3.224	3.224	3.224
	Transfer Gear Ratio 2WD / H4 / L4		—	—	1.000 / 1.000 / 2.618	1.000 / 1.000 / 2.618	
	Differential Gear Ratio (Front / Rear)		— / 3.909	— / 3.909	3.909 / 3.909	3.909 / 3.909	
	Differential Gear Size (Front / Rear)	mm (in.)	— / 252 (9.9)	— / 252 (9.9)	220 (8.7) / 252 (9.9)	220 (8.7) / 252 (9.9)	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type		Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	
	Brake Booster Type and Size	in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	
Proportioning Valve Type		—	—	—	—		
Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	
	Rear		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	
Stabilizer Bar	Front		Standard	Standard	Standard	Standard	
	Rear		Standard	Standard	Standard	Standard	
Steering Gear Type		Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion		
Steering Gear Ratio (Overall)		18.0	18.0	18.0	18.0		
Power Steering Type		Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type		

*1: Models without roof rack
*2: Towing package

*3: Leather package or models with Rear Seat Entertainment (RSE) system
*4: Transfer in 2WD or H4

*5: Transfer in L4
*6: Models with sliding roof

*7: Cold area specification

Item		Area	U.S.A.			
Body Type			Wagon			
Vehicle Grade			SRS	Limited	Platinum	
Model Code			USK65L-GKTSGA	USK65L-GKTLGA	USK65L-GKTZGA	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5210 (205.1)	5210 (205.1)	5210 (205.1)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0)
	Wheel Base		mm (in.)	3100 (122.0)	3100 (122.0)	3100 (122.0)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1755 (69.1)	1755 (69.1)	1755 (69.1)
	Effective Head Room	Front	mm (in.)	1009 (39.7), 973 (38.3)*6	1009 (39.7), 973 (38.3)*6	973 (38.3)
		Rear No. 1	mm (in.)	1000 (39.4), 988 (38.9)*6	1000 (39.4), 988 (38.9)*6	988 (38.9)
		Rear No. 2	mm (in.)	978 (38.5), 914 (36.0)*6	978 (38.5), 914 (36.0)*6	914 (36.0)
	Effective Leg Room	Front	mm (in.)	965 (38.0)	965 (38.0)	965 (38.0)
		Rear No. 1	mm (in.)	899 (35.4)	899 (35.4)	899 (35.4)
		Rear No. 2	mm (in.)	876 (34.5)	876 (34.5)	876 (34.5)
	Shoulder Room	Front	mm (in.)	1686 (66.4)	1686 (66.4)	1686 (66.4)
		Rear No. 1	mm (in.)	1678 (66.1)	1678 (66.1)	1678 (66.1)
		Rear No. 2	mm (in.)	1676 (66.0)	1676 (66.0)	1676 (66.0)
	Cargo Space	Length	mm (in.)	—	—	—
		Width	mm (in.)	—	—	—
		Height	mm (in.)	—	—	—
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)
Min. Running Ground Clearance		mm (in.)	254 (10.0)	254 (10.0)	244 (9.6)	
Angle of Approach		degrees	27.0	27.0	27.0	
Angle of Departure		degrees	21.0	21.0	21.0	
Curb Weight	Front	kg (lb)	1378 (3040)	1376 (3035)	1378 (3040)	
	Rear	kg (lb)	1335 (2945)	1338 (2950)	1342 (2960)	
	Total	kg (lb)	2714 (5985)	2714 (5985)	2721 (6000)	
Gross Vehicle Weight	Front	kg (lb)	1493 (3292)	1479 (3262)	1456 (3210)	
	Rear	kg (lb)	1788 (3943)	1802 (3973)	1825 (4025)	
	Total	kg (lb)	3281 (7235)	3281 (7235)	3281 (7235)	
Fuel Tank Capacity		ℓ (U.S.gal., Imp.gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	
Luggage Compartment Capacity (behind Front / Rear No. 1 / Rear No. 2 Seats)		m ³ (cu.ft.)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)	3.42 / 2.25 / 0.80 (120.8 / 79.4 / 28.4)	
Performance	Max. Speed		km / h (mph)	180 (111)	180 (111)	
	Max. Cruising Speed		km / h (mph)	180 (111)	180 (111)	
	Max. Permissible Speed	1st Gear	km / h (mph)	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5
			2nd Gear	km / h (mph)	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5
		3rd Gear	km / h (mph)	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5
		4th Gear	km / h (mph)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		5th Gear	km / h (mph)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		6th Gear	km / h (mph)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	—	—	—
		Curb to Curb	m (ft.)	11.9 (39.0)	11.9 (39.0)	11.9 (39.0)
Engine	Engine Type		3UR-FBE	3UR-FBE	3UR-FBE	
	Valve Mechanism		32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	
	Bore × Stroke	mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	
	Displacement	cm ³ (cu.in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)	
	Compression Ratio		10.2 : 1	10.2 : 1	10.2 : 1	
	Fuel System		SFI	SFI	SFI	
	Octane Rating		87 or higher	87 or higher	87 or higher	
	Max. Output (SAE-NET)	kW / rpm (HP / rpm)	284 / 5600 (381 / 5600)	284 / 5600 (381 / 5600)	284 / 5600 (381 / 5600)	
Max. Torque (SAE-NET)	N·m / rpm (ft·lb / rpm)	544 / 3600 (401 / 3600)	544 / 3600 (401 / 3600)	544 / 3600 (401 / 3600)		
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64	
	Generator Output	Watts	1560, 1800*3, 2160*2	1800, 2160*2	1800, 2160*2	
Chassis	Starter Output	kW	2.0	2.0	2.0	
	Clutch Type		—	—	—	
	Transmission Type		AB60F	AB60F	AB60F	
	Gear Ratio	In 1st		3.333	3.333	3.333
		In 2nd		1.960	1.960	1.960
		In 3rd		1.353	1.353	1.353
		In 4th		1.000	1.000	1.000
		In 5th		0.728	0.728	0.728
		In 6th		0.588	0.588	0.588
		In Reverse		3.061	3.061	3.061
	Transfer Gear Ratio 2WD / H4 / L4		1.000 / 1.000 / 2.618	1.000 / 1.000 / 2.618	1.000 / 1.000 / 2.618	
	Differential Gear Ratio (Front / Rear)		3.909, 4.300*2 / 3.909, 4.300*2	3.909, 4.300*2 / 3.909, 4.300*2	3.909, 4.300*2 / 3.909, 4.300*2	
	Differential Gear Size (Front / Rear)	mm (in.)	220 (8.7) / 252 (9.9)	220 (8.7) / 252 (9.9)	220 (8.7) / 252 (9.9)	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc
Parking Brake Type		Duo-servo Drum	Duo-servo Drum	Duo-servo Drum		
Brake Booster Type and Size	in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9		
Proportioning Valve Type		—	—	—		
Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	
	Rear		Double-wishbone	Double-wishbone	Double-wishbone	
Stabilizer Bar	Front		Standard	Standard	Standard	
	Rear		Standard	Standard	Standard	
Steering Gear Type		Rack and Pinion	Rack and Pinion	Rack and Pinion		
Steering Gear Ratio (Overall)		18.0	18.0	18.0		
Power Steering Type		Hydraulic Type	Hydraulic Type	Hydraulic Type		

*1: Models without roof rack
*2: Towing package

*3: Leather package or models with Rear Seat Entertainment (RSE) system
*4: Transfer in 2WD or H4

*5: Transfer in L4
*6: Models with sliding roof